

## PRIMER WB 31216NF WHITE 3585



Spraying



Waterborne

### PROPERTIES

Top of range polyester waterborne anticorrosion primer:

- Overcoatable with baked-on WB Base Coat AC and SB Base Coat.
- Excellent applicability particularly with electrostatic disk or bell cup.
- Excellent opacifying property.
- Excellent direct adhesion to aluminum.
- Accelerated drying process: 15' RT + 20' at 130°C.
- High spreading rate
- Low VOC

### RELATED BASE COATS

References

Baked-On  
WB Base  
Coat AC

### BASIS

Waterborne

### SUBSTRATES

Aluminum tubular frames

### TECHNOLOGY

Polyester

### Technical Data

<b>Solids by weight</b>	58 %
<b>VOC</b>	170 g.L <sup>-1</sup>
<b>Spreading rate m<sup>2</sup>/kg</b>	12,2 m <sup>2</sup> / 20 µm dry



## PRIMER WB 31433 BLACK 3948



Spraying



Waterborne

### PROPERTIES

Top of range polyester waterborne anticorrosion primer:

- Overcoatable with baked-on WB Base Coat AC and SB Base Coat.
- Excellent applicability particularly with electrostatic disk or bell cup.
- Excellent opacifying property.
- Excellent direct adhesion to aluminum.
- Accelerated drying process: 15' RT + 20' at 130°C.
- High spreading rate
- Low VOC

### RELATED BASE COATS

References

Baked-On  
WB Base  
Coat AC

### BASIS

Waterborne

### TECHNOLOGY

Polyester

### SUBSTRATES

Aluminum tubular frames

### Technical Data

<b>Solids by weight</b>	51 %
<b>VOC</b>	232 g.L <sup>-1</sup>
<b>Spreading rate m<sup>2</sup>/kg</b>	13,4 m <sup>2</sup> / 20 µm dry



alterpaint.com

**“Leading  
innovation  
in liquid  
coating”**

Think further





[www.alterpaint.com/fr/de/uk](http://www.alterpaint.com/fr/de/uk)

[contact@alterpaint.fr](mailto:contact@alterpaint.fr)  
[kontakt@alterpaint.de](mailto:kontakt@alterpaint.de)

Fr: +33 2 54 45 52 00  
Ger: +49 62 20 314 074  
Asia: +65 64 39 65 22

 **BARTOLAC**  
GROUPE